

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Kevin G. Jiang Art Unit :
Serial No. : Examiner :
Filed : Herewith
Title : CARRIER FOR DISK DRIVE HOT SWAPPING

Commissioner for Patents
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Prior to examination, please amend the application as follows:

In the specification:

Replace the paragraph beginning at page 1, line 1 with the following rewritten paragraph:

-- This application is a divisional of U.S. Serial Number 09/264,650, filed March 8, 1999, now pending issue. --

In the claims:

Cancel claims 1-17.

Amend claims 18-20 as follows:

18. (Amended) A method for inserting a disk drive into a peripheral bay chassis comprising:

receiving a disk drive into a base of a disk drive carrier, said base having an uppermost surface and being rotatably attached to a latching mechanism, wherein a lever can rotate between an open position and a closed position, said lever having comprising a lower engagement point and an upper engagement point:

CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No. EJ 932078108US

I hereby certify under 37 CFR §1.10 that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Commissioner for Patents, Washington, D.C. 20231.

Date of Deposit

Signature

Typed or Printed Name of Person Signing Certificate

inserting the carrier into a peripheral bay chassis slot while the lever is in an open position; and

securing the carrier to the peripheral bay chassis by rotating the lever to the closed position to extend the upper engagement point beyond the uppermost surface of the base and engage the peripheral bay chassis with and to extend the lower engagement point [and the upper engagement point] to engage the peripheral bay chassis.

19. (Amended) The method of claim 18 with the additional step of further comprising contacting an adjacent disk drive with at least one electrically conductive finger clip prior to engagement of a high speed back plane with a disk drive connector.

20. (Amended) The method of claim 18 with the additional step of further comprising depressing a release tab prior to rotating the lever into the closed position and releasing the release tab after engaging the lower engagement point.

Please add new claim 21 as follows:

21. A method for inserting a disk drive into a peripheral bay chassis comprising: receiving a disk drive into a base of a disk drive carrier, said base having an uppermost surface and being rotatably attached to a latching mechanism, wherein a lever can rotate between an open position and a closed position, said lever comprising a lower engagement point and an upper engagement point;

inserting the carrier into a peripheral bay chassis slot while the lever is in an open position;

depressing a release tab prior to rotating the lever into the closed position;

securing the carrier to the peripheral bay chassis by rotating the lever to the closed position to extend the upper engagement point beyond the uppermost surface of the base and engage the peripheral bay chassis and to extend the lower engagement point to engage the peripheral bay chassis;

releasing the release tab after engaging the lower engagement point; and

contacting an adjacent disk drive with at least one electrically conductive finger clip prior to engagement of a high speed back plane with a disk drive connector.

Applicant : Kevin G. Jiang
Serial No. :
Filed : Herewith
Page : 3

Attorney's Docket No.: 10559-003004 / P6716-DIV3


REMARKS

Attached is a marked-up version of the changes being made by the current amendment.

Applicant asks that all claims be examined.

Respectfully submitted,

Date: 12/31/01



David L. Feigenbaum
Reg. No. 30,378

Fish & Richardson P.C.
225 Franklin Street
Boston, Massachusetts 02110-2804
Telephone: (617) 542-5070
Facsimile: (617) 542-8906

20323510.doc

Version with markings to show changes made

In the claims:

Claims 1-17 have been cancelled.

Claims 18-20 have been amended as follows:

18. (Amended) A method for inserting a disk drive into a peripheral bay chassis comprising:

receiving a disk drive into a base of a disk drive carrier, said base having an uppermost surface and being rotatably attached to a latching mechanism, wherein a lever can rotate between an open position and a closed position, said lever [having] comprising a lower engagement point and an upper engagement point;

inserting the carrier into a peripheral bay chassis slot while the lever is in an open position; and

securing the carrier to the peripheral bay chassis by rotating the lever to the closed position to extend the upper engagement point beyond the uppermost surface of the base and engage the peripheral bay chassis [with] and to extend the lower engagement point [and the upper engagement point] to engage the peripheral bay chassis.

19. (Amended) The method of claim 18 [with the additional step of] further comprising contacting an adjacent disk drive with at least one electrically conductive finger clip prior to engagement of a high speed back plane with a disk drive connector.

20. (Amended) The method of claim 18 [with the additional step of] further comprising depressing a release tab prior to rotating the lever into the closed position and releasing the release tab after engaging the lower engagement point.